



www.senyacrushers.com

| Item | <u>Senya 5</u> | <u>Senya 6</u> | <u>Senya PP600</u> | <u>Senya PP128HC</u> | <u>Senya SP1</u> |
|---------------------------------|--|--|--|--|--|
| Configuration | Jaw crusher | Jaw Crusher | Jaw crusher | Impact Crusher | Screen Plant |
| Conveyor Belts | 1 discharge standard, Magnetic Metals Removal upgrade optional | Discharge and Magnetic standard equip | 3pc-fines, magnetic, material conveyor | 3pc-fines, magnetic (option), material conveyor | 3 |
| Total Power (required) | 33hp, 480v, 60 Hz | 47hp, 480v, 60Hz | 47hp, 480v, 60Hz | 59 hp, 480v, 60Hz | 10hp, 480v, 60Hz |
| Generator | SELF CONTAINED, 40KW, 55hp | 125hp, 100KW | 125hp, 100KW | 150hp, 125KW | 10KW |
| Electrical Control | Y, wireless remote standard | Y, wireless remote standard | Y | Yes | Y |
| Road Legal | Y | Y | Y | Y | Y |
| Capacity | ≤50 tph | ≤80 tph | ≤80 tph | ≤80 tph | ≤80 tph |
| Feeding Height | 9 ft | 11 ft | 12 ft | 12 ft | 4.5 ft |
| Feeding Size | < 16" | < 19" | <16" | 12" | <4" |
| Jaw Opening | 13" x 21" | 16" x 24" | 16" x 24" | N/A | N/A |
| Output Size | 3/8"~3"Minus | .5"~4" minus | 1"~4" minus | 0-6" | 5/8", 1.5", 3-4"Minus (Custom avail.) |
| Hopper Volume | 1.5 cu yds | 5 cu yds | 5 cu yds | 5 cu yds | .5 cu yds |
| Working Dimension(LxWxH) | 22' L x 8'.6' W x 9' H | 25.4' L x 8.2' W x 10.9' H | 28.3' L x 8.2' W x 11.7' H | 35.6' L x 9.1' W x 14.4'H | 23.2'L x 22.2' W x 8.5' H |
| Weight | 15,500 lbs | 16 T | 19T | 30T | 8000 lbs. |
| Crushing material | concrete, limestone, granite, river rock, asphalt, glass, granite countertop scrap, etc. | concrete, limestone, granite, river rock, asphalt etc. | concrete, limestone, granite, river rock, asphalt etc. | concrete, limestone, granite, river rock, asphalt etc. | concrete, sand, granite, asphalt, soil, etc. |
| Assembly time | 1 day | 1 days | one week | one week | 1 day |
| Portability | tire/ 3/4 Ton Pickup | tire/ Dump Truck/pintle hook | tire/ Semi/5th wheel | tire/ Semi/5th wheel | tire/ Pickup |
| Magnetic Metals Removal Convey | Optional Upgrade | Magnetic Conveyor Standard | Magnetic Conveyor | Magnetic Conveyor optional | N/A |
| Dust Suppression Upgrade | Optional Upgrade | | | | |
| Step Down Transformer 220v/110v | Optional Upgrade | | | | |
| | | | | | |
| | <u>S2318DOT</u> | <u>S2818DOT</u> | <u>S3024RY</u> | <u>S4024RY</u> | |
| Configuration | DOT Approved Portable Conveyor | DOT Approved Portable Conveyor | Radial Yard Conveyor | Radial Yard Conveyor | |
| Axle/Wheels | Fixed Solid | Fixed Solid | 90 degree rotating wheels | 90 degree rotating wheels | |
| Conveyor Length | 23' | 28' | 30' | 40' | |
| Discharge Height (Max) | 15' | 18' | 10' | 13' | |
| Adjustable Height | infinite hydraulic | infinite hydraulic | 2 position | 2 position | |
| Belt Width | 18" | 18" | 24" | 24" | |
| Road Legal | Yes | Yes | No | No | |
| Capacity | 80 tph | 80 tph | 100 tph | 100 tph | |
| Motor | 1.5 Hp 110V/460V | 1.5 Hp 110V/460V | 3 Hp 230/460V | 3 Hp 230/460V | |
| Hitch Type | 2" Ball | 2" Ball | Pintail Tow Hook | Pintail Tow Hook | |
| Loading Hopper | Yes | Yes | Yes | Yes | |
| Radial Yard Upgrade option | Optional Upgrade | Optional Upgrade | Standard | Standard | |